TECHNICAL SPECIFICATION LIGHTWEIGHT NATURAL FIBRE WALLCOVERING

Alhambra
Lightweight natural fibre wallcovering : non-woven cellulose / polyester fibre
90 grammes per square metre
53cm x 10.05m
Euroclass B
Tekfix 65
Damp back of product with water. Soak for 5 minutes. Apply adhesive to wall surface. Carefully smooth wallcovering onto wall surface using a felt roller roller, butt join lengths. Do not reverse hang. This product has a straight across match / 32cm vertical repeat. Allow to dry for 24 hours after hanging for optimum results
Lightweight natural fibre wallcoverings offer a wipeable finish and some resistance to knocks and scrapes. They are best used in 'low-traffic' areas and will retain their original appearance for 3 - 5 years, depending on area of use.
Always carry out a trial in an inconspicuous area first, to ensure cleaning agent is suitable. Clean with a mild non-soapy detergent with soft cloth or sponge. Do not use polishes, abrasive cleaning agents or strong cleaners as they will damage the surface, particularly the foil effects. Always clean from skirting level upwards. Rinse thoroughly with clean water (avoid over wetting). Individual stains should be removed as quickly as possible.
This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
Store at ambient temperatures away from heat source. Suitable lifting equipment may be required.
Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

TEKTURA WALLCOVERINGS

TEKTURA PLC, Suite 1.03 Harbour Island, 34 Harbour Exchange Square, London E14 9GE Tel 020 7536 3300 Fax 020 7536 3322