

TECHNICAL SPECIFICATION

NATURAL FIBRE FINISH WALLCOVERING

Design	Charleston
Description	Commercial quality non-woven cellulose/polyester fibre wallcovering
Weight	110 grammes per square metre
Roll Size	53cm x 10m
Fire Rating	EuroClass B
Adhesive	Tekfix 65
Hanging	Apply adhesive to wall surface. Carefully smooth wallcovering onto wall surface using a spatula or felt roller. Butt join. Charleston has an offset match, and a 32 vertical pattern repeat. Do not reverse hang.
Maintenance	<p>Natural fibre wallcoverings offer a wipeable easy-clean finish with medium resistance to knocks and scrapes. With regular cleaning they will retain their original appearance for 3-5 years depending on area of use.</p> <p>Always carry out a trial in an inconspicuous area first to ensure cleaning agent is suitable. Clean with a mild non-soapy detergent with soft cloth or sponge. Do not use polishes, abrasive cleaning agents, or strong active solvent cleaners as they will damage the surface. Always clean from the skirting level upwards. Rinse thoroughly with clean water (avoid over-wetting). Individual stains should be removed as quickly as possible.</p>
Health & Safety	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
Handling/Storage	Store at ambient temperatures away from heat source. Suitable lifting equipment may be required.
Fire Fighting	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
Ecological	This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

TEKTURA
WALLCOVERINGS

TEKTURA PLC, Suite 1.03 Harbour Island, 34 Harbour Exchange Square, London E14 9GE
Tel 020 7536 3300 Fax 020 7536 3322