TECHNICAL SPECIFICATION 53CM WIDE VINYL WALLCOVERING

Description N	Narrow width vinyl wallcovering with a paper backing.
Weight 3	330 grammes per square metre
Roll Size 5	52cm x 10.05m
Fire Rating C	Class 0 & 1 to BS476
Adhesive T	Tekfix 65
n	Apply adhesive to back of wallcovering. Fold and allow to soak for 5 minutes. Do not reverse hang alternate lengths. Butt join. Line the squares up to achieve a continuous effect.
S	Paper backed vinyls offer an easy-clean finish and some resistance to knocks and scrapes. They are best used in 'low-traffic' areas and will retain their original appearance for 3 - 5 years, depending on area of use.
s u s tł	Always carry out a trial in an inconspicuous area first, to ensure cleaning agent is suitable. Clean with a mild non-soapy detergent with soft cloth or sponge. Do not use polishes, abrasive cleaning agents or strong cleaners as they will damage the surface, particularly metallics. Always clean from skirting level upwards. Rinse horoughly with clean water (avoid over wetting). Individual stains should be removed as quickly as possible.
	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
	Store at ambient temperature away from heat source. Suitable lifting equipment may be required.
р	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
	This product is not bio-degradable. Dispose of in accordance with Local Authority Regulations or via an authorised contractor.

TEKTURA.

TEKTURA PLC, Suite 1.03 Harbour Island, 34 Harbour Exchange Square, London E14 9GE Tel 020 7536 3300 Fax 020 7536 3322