TECHNICAL SPECIFICATION FABRIC-BACKED VINYL WALLCOVERING

	Elements	
Description	Commercial quality vinyl wallcovering laminated onto a polyester cotton backing.	
Weight	355 grammes per square metre.	
Roll Size	130cm x 50m (sold in full rolls only)	
Fire Rating	Euroclass B when adhered to a suitable substrate / Class 0 & 1 to BS476 / IMO rated for marine use.	
Adhesive	Generally Tekfix Plus, though depends on substrate.	
Hanging	Apply adhesive to wall surface. Carefully smooth wallcovering onto wall surface using a spatula, allowing 5-10cm at top and bottom for trimming. Overlap lengths, and double cut through. All designs have a random pattern match. Remove any adhesive seepage <i>immediately</i> with detergent solution and clean water. Rinse thoroughly.	
	Reverse hang	Do not reverse hang
	34600 - 34604	34661 - 34662
	34620 - 34622	34680 - 34683
	34630 - 34633	
	34640 - 34644	
	34670 - 34674	
	34690 - 34692	
Maintenance	regular cleaning they will retain their origina area of use.	igh traffic levels, and will not tear easily. With I appearance for many years depending on area first, to ensure cleaning agent suitable. In soft cloth, sponge or soft bristle brush to polishes and abrasive cleaning agents as a texture, and can also damage metallic rs as they can stain and damage the vinyl I upwards. Rinse thoroughly with clean as quickly as possible. This wallcovering
Maintenance Health & Safety	scrapes. They are designed to withstand h regular cleaning they will retain their origina area of use. Always carry out a trial in an inconspicuous Clean with a mild non-soapy detergent with prevent build up of dirt and staining. Avoid p they will cause build up of dirt in the surface finishes. Avoid strong active solvent cleane surface. Always clean from the skirting leve water. Individual stains should be removed contains antimicrobials which guard against	igh traffic levels, and will not tear easily. With I appearance for many years depending on area first, to ensure cleaning agent suitable. In soft cloth, sponge or soft bristle brush to polishes and abrasive cleaning agents as texture, and can also damage metallic rs as they can stain and damage the vinyl I upwards. Rinse thoroughly with clean as quickly as possible. This wallcovering t mildew and bacterial growth.
	 scrapes. They are designed to withstand h regular cleaning they will retain their origina area of use. Always carry out a trial in an inconspicuous Clean with a mild non-soapy detergent with prevent build up of dirt and staining. Avoid p they will cause build up of dirt in the surface finishes. Avoid strong active solvent cleane surface. Always clean from the skirting leve water. Individual stains should be removed contains antimicrobials which guard agains This product is classified as non-hazardous 	igh traffic levels, and will not tear easily. With appearance for many years depending on area first, to ensure cleaning agent suitable. In soft cloth, sponge or soft bristle brush to polishes and abrasive cleaning agents as a texture, and can also damage metallic rs as they can stain and damage the vinyl d upwards. Rinse thoroughly with clean as quickly as possible. This wallcovering t mildew and bacterial growth. and therefore does not require any special ecial labelling.
Health & Safety	 scrapes. They are designed to withstand h regular cleaning they will retain their original area of use. Always carry out a trial in an inconspicuous Clean with a mild non-soapy detergent with prevent build up of dirt and staining. Avoid p they will cause build up of dirt in the surface finishes. Avoid strong active solvent cleane surface. Always clean from the skirting leve water. Individual stains should be removed contains antimicrobials which guard agains? This product is classified as non-hazardous handling. This product does not require specified at ambient temperatures away from her and the surface at ambient temperatures away from her area of use. 	igh traffic levels, and will not tear easily. With appearance for many years depending on area first, to ensure cleaning agent suitable. a soft cloth, sponge or soft bristle brush to polishes and abrasive cleaning agents as texture, and can also damage metallic rs as they can stain and damage the vinyl d upwards. Rinse thoroughly with clean as quickly as possible. This wallcovering t mildew and bacterial growth. and therefore does not require any special ecial labelling. heat source. Suitable lifting equipment may ar self contained breathing apparatus,

