

TECHNICAL SPECIFICATION

PAPER-BACKED VINYL WALLCOVERING

Product	WHITES Paper-backed designs : Ceramic, Circuit, Flow, Glaze, Grass, Mix, Ridge, Smooth, Solo, Touch
Description	Commercial quality, vinyl wallcovering laminated onto a paper backing.
Weight	300 grammes per square metre
Roll Size	130cm x 50m
Fire Rating	Euroclass B when adhered to a suitable substrate.
Adhesive	Generally Tekfix 65, though depends on substrate.
Hanging	Damp paper backing and allow to soak for 10 minutes. Apply adhesive to wall surface. Carefully smooth wallcovering onto wall surface using a spatula, allowing 5-10 cm at top and bottom for trimming. Overlap lengths and double cut through, using a seam roller to ensure product is well bonded at the join. Remove any adhesive seepage <i>immediately</i> with detergent solution and clean water. Rinse thoroughly. Each alternate length should be reverse hung with the exception of <u>Ridge which should not be reversed</u> .
Maintenance	<p>Paper-backed vinyls offer an easy-clean finish for most non oil-based stains, and some resistance to knocks and scrapes. They are best used in 'low traffic' areas. With regular cleaning they will retain their original appearance for 3 - 5 years, depending on area of use.</p> <p>Always carry out a trial in an inconspicuous area first, to ensure cleaning agent suitable. Clean with a mild non-soapy detergent with soft cloth, sponge or soft bristle brush to prevent build up of dirt and staining. Avoid polishes and abrasive cleaning agents as they will cause build up of dirt in the surface texture, and can also damage the surface texture, particularly metallics. Avoid strong active solvent cleaners as they can stain and damage the vinyl surface. Always clean from the skirting level upwards. Rinse thoroughly with clean water. Individual stains should be removed as quickly as possible.</p>
Health & Safety	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
Fire Fighting	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
Ecological	This product is not bio-degradable. Dispose of in accordance with Local Authority Regulations or via an authorised contractor.

TEKTURA
WALLCOVERINGS

TEKTURA PLC, Suite 1.03 Harbour Island, 34 Harbour Exchange Square, London E14 9GE
Tel 020 7536 3300 Fax 020 7536 3322