

TECHNICAL SPECIFICATION GRASSCLOTH WALLCOVERING

Product	Grasscloth
Description	Various natural fibres (grass, abaca, bamboo) laminated onto a paper backing.
Weight	Approximately 300 grammes per square metre
Roll Size	Supplied in rolls only Refs GCL00 to GCL39 – 90cm x 5.5m Others – 91.44cm x 10m
Adhesive	Tekfix 65
Hanging	Apply adhesive to back of wallcovering. Butt join lengths. Reverse hang. Specific hanging instructions are supplied to contractor with delivery.
Maintenance	Dust and grit should be removed using a soft brush or a vacuum cleaner with an upholstery attachment. Vacuum in the direction of the strands. To prevent stains, spills should be removed as quickly as possible using absorbent tissues (preferably white). Care should be taken not to push the liquid through the wallcovering. When using cleaning fluids, work from the edge of the stain inwards. Use small amounts of cleaning fluid and blot between applications to prevent overwetting. Always carry out an initial trial in an inconspicuous area.
Health & Safety	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
Handling/Storage	Store at ambient temperatures away from heat source. Suitable lifting equipment may be required.
Fire Fighting	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
Ecological	This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

TEKTURA
WALLCOVERINGS

TEKTURA PLC, Suite 1.03 Harbour Island, 34 Harbour Exchange Square, London E14 9GE
Tel 020 7536 3300 Fax 020 7536 3322