TECHNICAL SPECIFICATION NATURAL FIBRE FINISH WALLCOVERING

Design Absinth and Jive

Description Commercial quality non-woven cellulose/polyester fibre wallcovering

Weight 89 grammes per square metre

Roll Size 53cm x 10m

Fire Rating EuroClass B

Adhesive Tekfix 65

Hanging Apply adhesive to wall surface. Carefully smooth wallcovering onto wall surface

using a spatula or felt roller. Butt join. Absinth and Jive have an offset match,

and a 32 vertical pattern repeat. Do not reverse hang.

Maintenance Natural fibre wallcoverings offer a wipeable easy-clean finish with medium

resistance to knocks and scrapes. With regular cleaning they will retain their

original appearance for 3-5 years depending on area of use.

Always carry out a trial in an inconspicuous area first to ensure cleaning agent is suitable. Clean with a mild non-soapy detergent with soft cloth or sponge. Do not use polishes, abrasive cleaning agents, or strong active solvent cleaners as they will damage the surface. Always clean from the skirting level upwards. Rinse thoroughly with clean water (avoid over-wetting). Individual stains should

be removed as quickly as possible.

Health & Safety This product is classified as non-hazardous and therefore does not require any

special handling. This product does not require special labelling.

Handling/Storage Store at ambient temperatures away from heat source. Suitable lifting

equipment may be required.

Fire Fighting Any extinguishing media are suitable. Wear self contained breathing apparatus,

protective clothing and full face mask. Fumes should be ventilated immediately

due to possible liberation of noxious gases.

Ecological This product is not bio-degradable. Dispose of in accordance with Local

Authority regulations or via an authorised contractor.



TEKTURA PLC, Suite 1.03 Harbour Island, 34 Harbour Exchange Square, London E14 9GE Tel 020 7536 3300 Fax 020 7536 3322