TECHNICAL SPECIFICATION FABRIC-BACKED VINYL WALLCOVERING

Product	Extra Stain Resistant		
Description	Commercial quality vinyl wallcovering laminated onto a woven polycotton backing.		
Weight	450 - 460 grammes per square metre.		
Roll Size	130cm x 30m		
Fire Rating	Euroclass B / Class 0 and 1 to BS476 part 6 and 7		
Adhesive	Generally Tekfix Plus, though depends on substrate.		
Hanging	Apply adhesive to wall surface. Carefully smooth wallcovering onto wall surface using a spatula, allowing 5-10cm at top and bottom for trimming. Overlap lengths and double cut through. This pattern has a random pattern match. Reverse hang alternate lengths. Remove any adhesive seepage <i>immediately</i> with detergent solution and clean water. Rinse thoroughly.		
Maintenance	Extra Stain Resistant vinyls offer an easy-clean finish, and high resistance to knocks and scrapes. They are also designed to withstand high traffic levels, and will not tear easily. With regular cleaning they will retain their original appearance for many years depending on area of use. Along with all our fabric-backed wallcoverings, Extra Stain Resistant vinyls contain anti-microbials which are effective against a broad range of micro-organisms, including staphylococcus aureaus, klebsiella pneumonia, mucor racemosus and streptoverticillium reticulum		
	Recommendations for best results:		
	 Remove the contamination as soon as possible. Wet stains should be cleaned with absorbent paper or cloth. Work from the outer edges of the stain inwards, to keep the affected area as small as possible. In general, a cloth or sponge should work, if necessary use a soft brush. 		
	4: Always rinse off with clean water and ensure that the surface is dried afterwards		
	5: Avoid abrasive cleaners as these can affect the protective top layer		
	How to clean stains? A = Dry cloth B = Wet cloth / Water C = Water + mild detergent / All purpose cleaner D = Ethanol 40 % E = Chlorine bleach F = Turpentine / White spirit		
	Stain		
	Coffee B	Chocolate C	
	Ballpoint *1 D + E remove immediately	Candle wax D / F	
	Tea B	Rubber/Shoe sole C	
	Marker *1 D + E remove immediately	Oil / Butter / Fat C	
	Chocolate milk B	Shoe polish D	
	Fruit juices B	Gravy C	

Graphite pencil E	Urine/Urea A
Wine B	Ice C
Lipgloss D + E	Blood B
Tomato ketchup C	Salad dressing C
Betadine E	Mustard E
Potassium bromide 10% A	Egg C
Methylene blue 1% C * 1 Remove	
immediately	

The table above was established after extensive testing and offers guidelines for best results. It does not cover all types of stain, nor does it guarantee that any stain is 100% removable. Extra Stain Resistant is resistant to diluted acids and alkalis, but is not resistant to ketones (like acetone etc). Take care when using acetic acid. Check solvent content and components in professional cleaning agents and detergents before use. Test any cleaning agent on a small area of the wallcovering before general use. Please contact Tektura for further information and advice.

Always carry out a trial in an inconspicuous area first, to ensure cleaning agent suitable. For general cleaning, use a mild non-soapy detergent with soft cloth, sponge or soft bristle brush to prevent build up of dirt and staining. Avoid polishes and abrasive cleaning agents as they will cause build up of dirt in the surface texture, and can also damage metallic finishes. Always clean from the skirting level upwards. Rinse thoroughly with clean water. Individual stains should be removed as quickly as possible. This wallcovering contains antimicrobials which guard against mildew and bacterial growth.

- **Health & Safety** This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
- Handling/Storage Store at ambient temperatures away from heat source. Suitable lifting equipment may be required.
- **Fire Fighting** Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
- **Ecological** This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

TEKTURA WALLCOVERINGS

TEKTURA PLC, Suite 1.03 Harbour Island, 34 Harbour Exchange Square, London E14 9GE Tel 020 7536 3300 Fax 020 7536 3322