

# TECHNICAL SPECIFICATION

## LIGHTWEIGHT NATURAL FIBRE WALLCOVERING

---

<b>Design</b>	Rococo
<b>Description</b>	Lightweight natural fibre wallcovering : non-woven cellulose / polyester fibre Refs 9033/090 and 9033/040 have aluminium foil surface
<b>Weight</b>	190 grammes per square metre
<b>Roll Size</b>	52cm x 10.05m
<b>Fire Rating</b>	Euroclass B
<b>Adhesive</b>	Tekfix 65
<b>Hanging</b>	<p>Refs 9033/099 and 9033/070 Damp back of product with water. Soak for 5 minutes. Apply adhesive to wall surface. Carefully smooth wallcovering onto wall surface using a felt roller roller, butt join lengths. Do not reverse hang. This product has a straight across match / 18cm vertical pattern repeat. Allow to dry for 24 hours after hanging for optimum results.</p> <p>Refs 9033/090 and 9033/040 foil effects Totally smooth surface recommended as the reflective surface will show any irregularities. Damp back of product with water. Soak for 5 minutes. Apply adhesive to wall surface. Dark colours may need edges to be coloured to prevent white edges showing. Take care not to crease when folding. Carefully smooth wallcovering onto wall surface using a felt roller, butt joining lengths. Do not reverse hang. This product has a straight across match / 18cm vertical pattern repeat. Allow to dry for 24 hours after hanging for optimum results.</p>
<b>Maintenance</b>	<p>Lightweight natural fibre wallcoverings offer a wipeable finish and some resistance to knocks and scrapes. They are best used in 'low-traffic' areas and will retain their original appearance for 3 - 5 years, depending on area of use.</p> <p>Always carry out a trial in an inconspicuous area first, to ensure cleaning agent is suitable. Clean with a mild non-soapy detergent with soft cloth or sponge. Do not use polishes, abrasive cleaning agents or strong cleaners as they will damage the surface, particularly the foil effects. Always clean from skirting level upwards. Rinse thoroughly with clean water (avoid over wetting). Individual stains should be removed as quickly as possible. Foil effects - pat dry thoroughly.</p>
<b>Health &amp; Safety</b>	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
<b>Handling/Storage</b>	Store at ambient temperatures away from heat source. Suitable lifting equipment may be required.
<b>Fire Fighting</b>	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
<b>Ecological</b>	This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

---

TEKTURA  
WALLCOVERINGS

TEKTURA PLC, Suite 1.03 Harbour Island, 34 Harbour Exchange Square, London E14 9GE  
Tel 020 7536 3300 Fax 020 7536 3322