

TECHNICAL SPECIFICATION

OLEFIN WALLCOVERING

Product	Savannah
Description	Olefin finishing coat on non-woven backing. PVC-free.
Weight	420 grammes per square metre.
Roll Size	130cm x 50m
Fire Rating	Euroclass 13501, B s1 d0
Adhesive	Generally Tekfix Plus, though depends on substrate.
Hanging	Care should be taken during installation in order to produce optimum results. Apply adhesive to wall surface. Carefully smooth wallcovering onto wall surface using a spatula, allowing 5-10cm at top and bottom for trimming. Overlap lengths and double cut through. Run seamroller up join to ensure even adhesion. Remove any adhesive seepage <i>immediately</i> with detergent solution and clean water. Rinse thoroughly. Refer to roll for hanging instructions. Burlap has a random pattern match.
Maintenance	<p>Olefin wallcoverings offer an easy-clean finish, and high resistance to knocks and scrapes. They are designed to withstand high traffic levels and will not tear easily. With regular cleaning they will retain their original appearance for many years depending on area of use.</p> <p>Always carry out a trial in an inconspicuous area first, to ensure cleaning agent suitable. Wipe with a mild non-soapy detergent with soft cloth or sponge to prevent build up of Savdirt and staining. Avoid polishes and abrasive cleaning agents as they will cause build up of dirt in the surface texture. Avoid strong active solvent cleaners as they can stain and damage the Olefin surface. Always clean from the skirting level upwards. Rinse thoroughly with clean water. Individual stains should be removed as quickly as possible. Diluted bleach can be used.</p>
Health & Safety	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
Handling/Storage	Store at ambient temperatures away from heat source. Suitable lifting equipment may be required.
Fire Fighting	Any extinguishing media are suitable. Wear self-contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
Ecological	This product is not biodegradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor. EPD on request.

TEKTURA

TEKTURA Ltd, 34 Harbour Exchange Square, London E14 9GE
Tel 020 7536 3300 info@tektura.com