TECHNICAL SPECIFICATION FABRIC-BACKED VINYL WALLCOVERING

Product Stone Age

Description Commercial quality vinyl laminated on a woven cotton backing. 13% recycled content.

Weight 490 grammes per square metre.

Roll Size 130cm x 35m

Fire Rating Euroclass 13501, B s2 d0

Adhesive Generally Tekfix Plus, though depends on substrate. Tekfix VOV should be used when

installing around right-angled corners.

Hanging Care should be taken during installation in order to produce optimum results. Apply

adhesive to wall surface. Carefully smooth wallcovering onto wall surface using a spatula, allowing 5-10cm at top and bottom for trimming. Overlap lengths and double cut through. Run seamroller up join to ensure even adhesion. Remove any adhesive seepage *immediately* with detergent solution and clean water. Rinse thoroughly.

Refer to roll for hanging instructions. Stone Age has a random pattern match.

Maintenance Fabric-backed vinyls offer an easy-clean finish, and high resistance to knocks and

scrapes. They are designed to withstand high traffic levels and will not tear easily. With regular cleaning they will retain their original appearance for many years

depending on area of use.

Always carry out a trial in an inconspicuous area first, to ensure cleaning agent suitable. Clean with a mild non-soapy detergent with soft cloth, sponge or soft bristle brush to prevent build up of dirt and staining. Avoid polishes and abrasive cleaning agents as they will cause build up of dirt in the surface texture and can also damage metallic finishes. Avoid strong active solvent cleaners as they can stain and damage the vinyl surface. Always clean from the skirting level upwards. Rinse thoroughly with clean

water. Individual stains should be removed as quickly as possible. Diluted bleach can

be used.

Health & Safety This product is classified as non-hazardous and therefore does not require

any special handling. This product does not require special labelling.

Handling/Storage Store at ambient temperatures away from heat source. Suitable lifting equipment may

be required.

Fire Fighting Any extinguishing media are suitable. Wear self-contained breathing apparatus,

protective clothing and full face mask. Fumes should be ventilated immediately due to

possible liberation of noxious gases.

Ecological This product is not biodegradable. Dispose of in accordance with Local

Authority regulations or via an authorised contractor.

TEKTURA

TEKTURA Ltd, 34 Harbour Exchange Square, London E14 9GE Tel 020 7536 3300 info@tektura.com