

# TECHNICAL SPECIFICATION

## ZINTRA ACOUSTIC PANEL 12mm

---

<b>Product</b>	Zintra Acoustic 12mm panel
<b>Description</b>	100% polyester / matte finish.
<b>Weight</b>	2.4kg per m2 (approx 8kg per sheet)
<b>Panel Size</b>	2800mm x 1225mm x 12mm
<b>Acoustic Rating</b>	aw 0.30 - 0.95 / NRC 0.45 - 0.90
<b>Fire Rating</b>	Euroclass B
<b>Installation</b>	<p><b>For Zintra Textures :</b> Adhere to substrate with silicone based construction adhesive such as GripFix SF or PinkGrip SF.</p> <p><b>For Zintra 12mm panels / Zintra on Zintra patterns :</b> Adhere to substrate with silicone based construction adhesive such as GripFix SF or PinkGrip SF. Alternatively attach with Z-clips, screws, stand-offs, aluminium trim or timber moulding.</p>
<b>Application</b>	Indoor areas only.
<b>Colourfastness</b>	In accordance with AATCC 16.3 option 3, the colour change at 20 AFU was 4.5.
<b>Maintenance</b>	Vacuum to remove dust.
<b>Health &amp; Safety</b>	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
<b>Handling/Storage</b>	Zintra acoustic panels must be stored in a cool, dry, well ventilated area, out of direct sunlight and away from heat sources. During storage keep covered (eg with polythene sheet) at all times. Panels should be stored horizontally. Pallets should not be stacked.
<b>Fire Fighting</b>	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
<b>Ecological</b>	This product is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.

---

**TEKTURA**  
WALLCOVERINGS

TEKTURA PLC, Suite 1.03 Harbour Island, 34 Harbour Exchange Square, London E14 9GE  
Tel 020 7536 3300 Fax 020 7536 3322