

TECHNICAL SPECIFICATION

ZINTRA ACOUSTIC PANEL 12mm

Product	Zintra Acoustic 12mm panel
Description	100% recyclable polyester / 60% post-consumer recycled PET. Matte finish.
Weight	2.4kg per m2 (approx 8kg per sheet)
Panel Size	2800mm x 1225mm x 12mm
Acoustic Rating	aw 0.30 - 0.85 / NRC 0.45 - 0.90
Fire Rating	Euroclass B
Installation	<p>For Zintra Textures: Adhere to substrate with silicone based construction adhesive such as GripFix SF or PinkGrip SF.</p> <p>For Zintra 12mm panels / Zintra on Zintra patterns: Adhere to substrate with silicone-based construction adhesive such as GripFixSF or PinkGripSF. Alternatively attach with Z-clips, screws, stand-offs, aluminium trim or timber moulding.</p>
Application	Indoor areas only.
Colourfastness	In accordance with AATCC 16.3 option 3, colour change at 20 AFU was 4.5.
Maintenance	Vacuum to remove dust. Surface can be disinfected by spraying with diluted bleach solution (4 teaspoons per 0.95 litres water). Wipe off surface moisture.
Health & Safety	This product is classified as non-hazardous and therefore does not require any special handling. This product does not require special labelling.
Handling/Storage	Zintra acoustic panels must be stored in a cool, dry, well ventilated area, out of direct sunlight and away from heat sources. During storage keep covered (eg with polythene sheet) at all times. Panels should be stored horizontally. Pallets should not be stacked.
Fire Fighting	Any extinguishing media are suitable. Wear self contained breathing apparatus, protective clothing and full face mask. Fumes should be ventilated immediately due to possible liberation of noxious gases.
Ecological	This product is 100% recyclable polyester. Zintra is not bio-degradable. Dispose of in accordance with Local Authority regulations or via an authorised contractor.